

1778-VXL 3/4" VIBROTHERM DRIVE[®] COMPOSITE IMPACT WRENCH

VIBROTHERM
by AIRCAT DRIVE[®]



1778-VXLBB
AIRCAT[®] VIBROTHERM DRIVE[®] Boot
Fits Model: 1778-VXL

FEATURES & SPECIFICATIONS

- Provides 1,450 ft-lb maximum torque and 1,700 ft-lb of loosening torque
- VIBROTHERM DRIVE[®] impact wrenches incorporates the new patented AIRCAT design impact wrench mechanism
- The patented Vibrotherm hammer mechanism reduces vibration levels by 30%-40% and increases the life of the tool by 50%
- The latest patented AIRCAT muffler system provides the AIRCAT's unmatched low noise levels
- The patented grip design provides the customary AIRCAT operator comfort
- Investment in tooling, materials, and the triple injection molding processes enables AIRCAT[®] to produce cosmetic designs that are unmatched in the industry

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max. Torque (ft-lb) @90 psi	Weight (lbs.)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet NPT (in.)
1778-VXL	5,400	1	3/4	1300	1450	7.70	7.70	8	1/2	3/8