

1993-1-VXL 1" VIBROTHERM DRIVE[®] COMPOSITE STRAIGHT IMPACT WRENCH

VIBROTHERM
by AIRCAT[®] **DRIVE[®]**



FEATURES & SPECIFICATIONS

- Provides 2,100 ft-lb maximum torque and 2,300 ft-lb of loosening torque
- VIBROTHERM DRIVE[®] impact wrenches incorporate the new patented AIRCAT[®] design impact wrench mechanism
- The new mechanism reduces vibration levels by 30%-40% and increases the life of the mechanism by 50%
- 6,000 RPM Free Speed
- Unmatched power-to-weight ratio
- Rubber handle grip and rubberized trigger inserts for ultimate comfort
- Combined friction-ring and through-hole socket retainer
- Tooling, materials, and the triple injection molding processes enables AIRCAT[®] to produce cosmetic designs that are unmatched in the industry

Model No.	Free Speed (RPM)	Bolt Capacity (in.)	Square Drive (in.)	Impacts Per Minute	Max. Torque (ft-lb) @90 psi	Weight (lbs.)	Length (in)	Air Cons. (CFM)	Rec. Hose Size (in.)	Air Inlet NPT (in.)
1993-1-VXL	6,000	1-1/4	1	950	2100	18.50	13.40	10	1/2	1/2